

4.3 TABLE OF DIMENSIONAL REQUIREMENTS (Except as provided for in Section VIII)

Districts	MINIMUM LOT DIMENSIONS ^a			MINIMUM SETBACK DIMENSIONS ^a			Max. Height of Structure	Max.% Bldg. Cvge/ Lot	Min.% Open Space/ Lot
	Area	Continuous Frontage ^d	Depth	Front	Side	Rear			
R-4 ^b	120,000	300	200	60	30	60	35	20	70
R-3 ^b	120,000	300	200	60	30	60	35	20	70
R-2 ^b	80,000 ^d	250	140	40	20	40	35	30	30
R-1 ^b	60,000 ^e	160	120	30	15	40	35	30	30
R-1 (other than Res.)	15,000	100	100	25	15	40	35	30	50
B-1 ^{c k}	15,000 ^f	80	80	30	15	40	35	40	30
M-1 ^{c k}	110,000	250	300	50	40 ^h	50	45	40	30
VR-1 ⁱ	15,000 ⁱ	80	80	30	15	40	35	40	30
VB-1 ^{i j}	7,500 ⁱ	50	100	0	10	10	35	60	20
VM-1 ^l	55,000	150	200	25	25	25	35	50	30

See Explanatory Notes in Section 4.3 for footnoted items.

4.3 EXPLANATORY NOTES

The following explanatory notes shall provide further definitions for the footnoted items in Table 4.2.

- a. All measurements are in feet unless otherwise noted.
- b. These dimensions shall not apply to Conservation Subdivisions. See Section VIII for applicable dimensional requirements.
- c. When the footnoted commercial or industrial uses abut residential uses or a residential district, the minimum front and rear setbacks shall be 100 feet from and the side setback shall be 50 feet from a property line abutting a residential use or district.
- d. 80,000 sq. ft. + 16,000 sq. ft. for each dwelling unit more than one on a lot.
- e. 60,000 sq. ft. + 8,000 sq. ft. for each dwelling unit more than one on a lot.
- f. 15,000 sq. ft. + 2,000 sq. ft. for each dwelling unit more than one on a lot.
- g. The minimum lot width at the front yard setback line shall not be less than 85 percent of the minimum lot frontage required for the District. The frontage on a road at a cul-de-sac may be less than specified if the lot width at the depth of the front yard setback line meets the minimum lot frontage requirements, but in no event less than 30 feet.
- h. For residential use only in the M-1 zone the sideline setback shall be 30 feet.
- i. The required square footage of land area for the first dwelling unit shall be equal to the minimum lot area as defined in the Table of Dimensional Requirements. For each additional dwelling unit an additional 2,000 square feet of land area shall be required.
- j. When the footnoted commercial or industrial uses abut residential uses or a residential district or are situated in a residential area, the minimum front setback shall be 25 feet and the minimum side setback shall be 25 feet from a property line abutting a residential use or district.
- k. In the B-1 and M-1 zones, the maximum gross floor area of commercial retail stores and restaurants shall not exceed 40,000 square feet.
- l. In the VB-1 and VM-1 zones, the maximum gross floor area of commercial retail stores and restaurants shall not exceed 20,000 square feet.

4.4 SPECIAL DIMENSIONAL AND DENSITY CONDITIONS

The following special conditions shall apply as appropriate to this Section of this Ordinance.

4.4.1 Detached Accessory Building: In all districts, a detached accessory building shall conform to the following provisions:

- (a) It shall not be less than the front setback for the district or less than 10 feet from any other lot line or from any principal or accessory building.
- (b) It shall not exceed 20 feet in height unless the accessory is placed to comply with principal building setback in which case it will conform to the height restriction of the district.